



SIMATIC ET 200SP, PROFINET, 2-port interface module IM 155-6PN/2 High Feature, 1 slot for BusAdapter, max. 64 I/O modules and 16 ET 200AL modules, S2 redundancy, multi-hotswap, 0.25 ms, isochronous mode, optional PN strain relief, including server module

General information	
Product type designation	IM 155-6 PN/2 HF
HW functional status	From FS02
Firmware version	V4.2
<ul style="list-style-type: none"> <li>FW update possible</li> </ul>	Yes
Product function	
<ul style="list-style-type: none"> <li>I&amp;M data</li> </ul>	Yes; I&M0 to I&M3
<ul style="list-style-type: none"> <li>Module swapping during operation (hot swapping)</li> </ul>	Yes; Multi-hot swapping
<ul style="list-style-type: none"> <li>Isochronous mode</li> </ul>	Yes
<ul style="list-style-type: none"> <li>Tool changer</li> </ul>	Yes; Docking station and docking unit
Engineering with	
<ul style="list-style-type: none"> <li>STEP 7 TIA Portal configurable/integrated from version</li> </ul>	V15.1
<ul style="list-style-type: none"> <li>STEP 7 configurable/integrated from version</li> </ul>	use GSD file
<ul style="list-style-type: none"> <li>PROFINET from GSD version/GSD revision</li> </ul>	GSDML V2.34
Configuration control	
via dataset	Yes
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes
Short-circuit protection	Yes
Mains buffering	
<ul style="list-style-type: none"> <li>Mains/voltage failure stored energy time</li> </ul>	10 ms
Input current	
Current consumption, max.	700 mA
Inrush current, max.	4.5 A
$I^2t$	0.25 A <sup>2</sup> ·s
Power loss	
Power loss, typ.	2.4 W
Address area	
Address space per module	
<ul style="list-style-type: none"> <li>Address space per module, max.</li> </ul>	288 byte; For input and output data respectively
Address space per station	
<ul style="list-style-type: none"> <li>Address space per station, max.</li> </ul>	1 440 byte
Hardware configuration	
Rack	
<ul style="list-style-type: none"> <li>Quantity of operable ET 200SP modules, max.</li> </ul>	64
<ul style="list-style-type: none"> <li>Quantity of operable ET 200AL modules, max.</li> </ul>	16
Submodules	

• Number of submodules per station, max. 256

## Interfaces

Number of PROFINET interfaces 1; 2 ports (switch)

### 1. Interface

#### Interface types

- RJ 45 (Ethernet) Yes; with BusAdapter
- Number of ports 2; with BusAdapter
- integrated switch Yes
- BusAdapter (PROFINET) Yes; BA 2x RJ45, BA 2x FC, BA 2x SCRJ, BA SCRJ/RJ45, BA SCRJ/FC, BA 2x LC, BA LC/RJ45, BA LC/FC

#### Protocols

- PROFINET IO Device Yes
- Open IE communication Yes
- Media redundancy Yes; PROFINET MRP client

#### PROFINET IO Device

##### Services

- IRT Yes; 250 µs to 4 ms in 125 µs frame
- PROFIenergy Yes
- Prioritized startup Yes
- Shared device Yes
- Number of IO Controllers with shared device, max. 4

### Interface types

#### RJ 45 (Ethernet)

- Transmission procedure PROFINET with 100 Mbit/s full duplex (100BASE-TX)
- 100 Mbps Yes
- Autonegotiation Yes
- Autocrossing Yes

#### Protocols

Supports protocol for PROFINET IO Yes

PROFIsafe Yes

PROFIBUS No

EtherNet/IP No

Modbus TCP No

#### Number of connections

- Number of MtM communication relationships/connections, max. 16

#### Redundancy mode

- PROFINET system redundancy (S2) Yes; NAP S2
- H-Sync forwarding Yes

#### Media redundancy

- MRP Yes
- MRPD No

#### Open IE communication

- TCP/IP Yes
- SNMP Yes
- LLDP Yes

### Isochronous mode

Equidistance Yes

shortest clock pulse 250 µs

max. cycle 4 ms

Bus cycle time (TDP), min. 250 µs

Jitter, max. 1 µs

### Interrupts/diagnostics/status information

Status indicator Yes

Alarms Yes

Diagnostics function Yes

#### Diagnostics indication LED

- RUN LED Yes; green LED
- ERROR LED Yes; red LED
- MAINT LED Yes; Yellow LED
- Monitoring of the supply voltage (PWR-LED) Yes; green PWR LED

• Connection display LINK TX/RX	Yes; 2x green link LEDs on BusAdapter	
<b>Potential separation</b>		
between backplane bus and electronics	No	
between PROFINET and all other circuits	Yes; 1500 V AC (type test)	
between supply and all other circuits	No	
<b>Permissible potential difference</b>		
between different circuits	Safety extra low voltage SELV	
<b>Isolation</b>		
Isolation tested with	707 V DC (type test)	
<b>Standards, approvals, certificates</b>		
Network loading class	3	
<b>Ecological footprint</b>		
• environmental product declaration	Yes	
<b>Global warming potential</b>		
— global warming potential, (total) [CO2 eq]	105 kg	
— global warming potential, (during production) [CO2 eq]	13.7 kg	
— global warming potential, (during operation) [CO2 eq]	91.9 kg	
— global warming potential, (after end of life cycle) [CO2 eq]	-0.617 kg	
<b>Ambient conditions</b>		
<b>Ambient temperature during operation</b>		
• horizontal installation, min.	-30 °C; No condensation	
• horizontal installation, max.	60 °C	
• vertical installation, min.	-30 °C; No condensation	
• vertical installation, max.	50 °C	
<b>Altitude during operation relating to sea level</b>		
• Installation altitude above sea level, max.	5 000 m; Restrictions for installation altitudes > 2 000 m, see manual	
<b>connection method</b>		
<b>ET-Connection</b>		
• via BU/BA Send	Yes; + 16 ET 200AL modules	
<b>Mechanics/material</b>		
Strain relief	Yes; Optional	
<b>Dimensions</b>		
Width	50 mm	
Height	117 mm	
Depth	74 mm	
<b>Weights</b>		
Weight, approx.	120 g; without BusAdapter	
<b>Classifications</b>		
	<b>Version</b>	<b>Classification</b>
eClass	14	27-24-26-08
eClass	12	27-24-26-08
eClass	9.1	27-24-26-08
eClass	9	27-24-26-08
eClass	8	27-24-26-08
eClass	7.1	27-24-26-08
eClass	6	27-24-26-08
ETIM	10	EC001604
ETIM	9	EC001604
ETIM	8	EC001604
ETIM	7	EC001604
IDEA	4	3564
UNSPSC	15	32-15-17-05
<b>Approvals / Certificates</b>		
<b>General Product Approval</b>		

[Miscellaneous](#)



[Manufacturer Declaration](#)

[PROFINET](#)



General Product Approval

For use in hazardous locations

[KC](#)



[EM](#)

[CCC-Ex](#)



For use in hazardous locations

Maritime application



IECEX

[Miscellaneous](#)

[Type Examination Certificate](#)



ABS



BUREAU VERITAS



DNV

Maritime application



LRS

[NK / Nippon Kaiji Kyokai](#)



RINA



RMRS

[CCS \(China Classification Society\)](#)



KR

Environment

Industrial Communication



[PROFINET](#)

last modified:

10/23/2025