

Zdjęcie jest reprezentatywne

Eaton 189869

Eaton Moeller® series PKZM0 Motor-protective circuit-breaker (-EA), 12.5 kW, 20 - 25 A, Screw terminals

General specifications

PRODUCT NAME	Eaton Moeller® series PKZM0 Motor-protective circuit-breaker
CATALOG NUMBER	189869
EAN	4015081878659
PRODUCT LENGTH/DEPTH	76 mm
PRODUCT HEIGHT	93 mm
PRODUCT WIDTH	45 mm
PRODUCT WEIGHT	0.294 kg
COMPLIANCES	RoHS conform CE Marked
MODEL CODE	PKZM0-25-EA

Features & Functions

ACTUATOR TYPE	Turn button
FEATURES	Phase-failure sensitivity (according to IEC/EN 60947-4-1, VDE 0660 Part 102)
FUNCTIONS	Phase failure sensitive
NUMBER OF POLES	Three-pole

General information

CONNECTION	Screw terminals
LIFESPAN, ELECTRICAL	100,000 operations
LIFESPAN, MECHANICAL	100,000 Operations
MOUNTING POSITION	Can be snapped on to IEC/EN 60715 top-hat rail with 7.5 or 15 mm height.
OPERATING FREQUENCY	40 Operations/h
OVERVOLTAGE CATEGORY	III
POLLUTION DEGREE	3
PRODUCT CATEGORY	Motor protective circuit breaker
PRODUCT CATEGORY	Motor protective circuit breaker
PROTECTION	Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274)
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	6000 V AC
SHOCK RESISTANCE	25 g, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms
SUITABLE FOR	Branch circuit: Suitable for group installations, (UL/CSA) Also motors with efficiency class IE3
TEMPERATURE COMPENSATION	-5 - 40 °C to IEC/EN 60947, VDE 0660 -25 - 55 °C, Operating range ≤ 0.25 %/K, residual error for T > 40°

Climatic environmental conditions

AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MIN	-25 °C
AMBIENT STORAGE TEMPERATURE - MIN	-40 °C
AMBIENT STORAGE TEMPERATURE - MAX	80 °C
CLIMATIC PROOFING	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30

Electrical rating

RATED FREQUENCY - MIN	50 Hz
RATED FREQUENCY - MAX	60 Hz
RATED OPERATIONAL POWER AT AC-3E, 220/230 V, 50 HZ	5.5 kW
RATED OPERATIONAL POWER AT AC-3E, 380/400 V, 50 HZ	12.5 kW
RATED OPERATIONAL VOLTAGE (UE) - MIN	690 V
RATED OPERATIONAL VOLTAGE (UE) - MAX	690 V
RATED UNINTERRUPTED CURRENT (IU)	25 A

Terminal capacities

TERMINAL CAPACITY (SOLID)	1 x (1 - 6) mm ² 2 x (1 - 6) mm ²
TERMINAL CAPACITY (SOLID/STRANDED AWG)	18 - 10
STRIPPING LENGTH (MAIN CABLE)	10 mm
TIGHTENING TORQUE	1.7 Nm, Screw terminals, Main cable

Short-circuit rating

RATED SHORT-CIRCUIT BREAKING CAPACITY ICU AT 400 V AC	50 kA
RATED SHORT-CIRCUIT BREAKING CAPACITY ICS AT 400 V AC	38 kA
RATED SHORT-CIRCUIT BREAKING CAPACITY ICU AT 440 V AC	10 kA
RATED SHORT-CIRCUIT BREAKING CAPACITY ICS AT 440 V AC	3 kA
RATED SHORT-CIRCUIT BREAKING CAPACITY ICU AT 500 V AC	3 kA
RATED SHORT-CIRCUIT BREAKING CAPACITY ICS AT 500 V AC	3 kA
RATED SHORT-CIRCUIT BREAKING CAPACITY ICU AT 690 V AC	3 kA
RATED SHORT-CIRCUIT BREAKING CAPACITY ICS AT 690 V AC	1 kA
SHORT-CIRCUIT CURRENT RATING (GROUP PROTECTION)	10 kA, 600 V High Fault, Fuse, SCCR (UL/CSA) with 150 A, 600 V High Fault, Fuse, SCCR (UL/CSA) 10 kA, 600 V High Fault, CB, SCCR (UL/CSA) with 125 A, 600 V High Fault, CB, SCCR (UL/CSA) 18 kA, 600 V High Fault, Fuse with CL, SCCR (UL/CSA) with 600 A, 600 V High Fault, Fuse with CL, SCCR (UL/CSA) 18 kA, 600 V High Fault, CB

with CL, SCCR (UL/CSA)
with 600 A, 600 V High
Fault, CB with CL, SCCR
(UL/CSA)
18 kA, 480 V High Fault,
CB, SCCR (UL/CSA) with
600 A, 480 V High Fault,
CB, SCCR (UL/CSA)
18 kA, 480 V High Fault,
Fuse, SCCR (UL/CSA) with
600 A, 480 V High Fault,
Fuse, SCCR (UL/CSA)

Basic device fixed 15.5 x lu

SHORT-CIRCUIT RELEASE

± 20% tolerance
388 A, I_{rm}

Switching capacity

SWITCHING CAPACITY 25 A, AC-3 up to 690 V

Motor rating

**ASSIGNED MOTOR
POWER AT 230/240 V, 60
HZ, 3-PHASE** 7.5 HP

**ASSIGNED MOTOR
POWER AT 460/480 V, 60
HZ, 3-PHASE** 15 HP

**ASSIGNED MOTOR
POWER AT 575/600 V, 60
HZ, 3-PHASE** 20 HP

Trip blocks

**OVERLOAD RELEASE
CURRENT SETTING - MIN** 20 A

**OVERLOAD RELEASE
CURRENT SETTING - MAX** 25 A

Design verification

**EQUIPMENT HEAT
DISSIPATION, CURRENT-
DEPENDENT PVID** 7.04 W

**HEAT DISSIPATION
CAPACITY PDISS** 0 W

**HEAT DISSIPATION PER
POLE, CURRENT-
DEPENDENT PVID** 2.3 W

**RATED OPERATIONAL
CURRENT FOR SPECIFIED
HEAT DISSIPATION (IN)** 25 A

**STATIC HEAT
DISSIPATION, NON-
CURRENT-DEPENDENT
PVS** 0 W

Do pobrania

CHARACTERISTIC CURVE	eaton-manual-motor-starters-pkz-characteristic-curve.eps
	eaton-manual-motor-starters-characteristic-characteristic-curve-008.eps
DEKLARACJE ZGODNOŚCI	eaton-motor-protective-circuit-breaker-declaration-of-conformity-uk251169en.pdf
	eaton-motor-protective-circuit-breaker-declaration-of-conformity-eu250686en.pdf
INSTRUKCJE MONTAŻU	IL034046ZU
MODELE ECAD	ETN.189869.edz
MODELE MCAD	DA-CD-pkzm0
	DA-CS-pkzm0
RYSUNKI	eaton-manual-motor-starters-pkz-dimensions-003.eps
	eaton-manual-motor-starters-pkz-dimensions-002.eps
	eaton-manual-motor-starters-pkz-dimensions.eps
	eaton-manual-motor-starters-pkzm0-3d-drawing-008.eps
	eaton-manual-motor-starters-circuit-breaker-pkzm0-3d-drawing.eps
SCHEMATY POŁĄCZEŃ	eaton-manual-motor-starters-transformer-pkzm0-wiring-diagram.eps

NAZWA PROJEKTU:

NUMER PROJEKTU:

PRZYGOTOWANE PRZEZ:

DATA:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Irlandia
Eaton.com

© 2026 Eaton. Wszelkie prawa zastrzeżone.

Najnowsze informacje o produktach i wsparciu znajdują się na naszych mediach społecznościowych.

