



**Automatización Eléctrica**

Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#)

## General Information

<b>Extended Product Type:</b>	MS497-63
<b>Product ID:</b>	1SAM580000R1007
<b>EAN:</b>	4013614265631
<b>Catalog Description:</b>	MS497-63 Manual Motor Starter
<b>Long Description:</b>	The MS497-630 manual motor starter is a 70 mm width devices with a rated operational current of $I_e = 63.0$ A. This device is used to manually switch on and off motors and to protect them reliably and without the need for a fuse from short-circuits, overload and phase failures. The manual motor starter offers a rated service short-circuit breaking capacity $I_{cs} = 50$ kA at 400 VAC and the trip class 10. Further features are the build-in disconnect function, temperature compensation, trip-free mechanism and a rotary handle with a clear switch position indication. The manual motor starter is suitable for three- and single-phase applications. The handle is lockable to protect against unauthorized changes. Auxiliary contacts, signalling contacts, undervoltage releases and shunt trips are available as accessory.

## Categories

Products » Low Voltage Products and Systems » Circuit Breakers » Manual Motor Starters
Products » Low Voltage Products and Systems » Control Products » Manual Motor Starters » Manual Motor Starters

## Ordering

<b>EAN:</b>	4013614265631
<b>Minimum Order Quantity:</b>	1 piece
<b>Customs Tariff Number:</b>	85362010

## Dimensions

<b>Product Net Width:</b>	70 mm
<b>Product Net Height:</b>	165 mm
<b>Product Net Depth:</b>	174 mm
<b>Product Net Weight:</b>	2.255 kg

## Container Information

<b>Package Level 1 Units:</b>	1 piece
<b>Package Level 1 Width:</b>	76.5 mm
<b>Package Level 1 Height:</b>	171 mm
<b>Package Level 1 Length:</b>	190 mm
<b>Package Level 1 Gross Weight:</b>	2.242 kg

## Environmental

<b>Ambient Air Temperature:</b>	Operation -20 ... +70 °C Operation Compensated -20 ... +60 °C Storage -50 ... +80 °C
<b>Ambient Air Temperature Compensation:</b>	Yes
<b>Maximum Operating Altitude Permissible:</b>	2000 m
<b>Resistance to Shock acc. to IEC 60068-2-27:</b>	11 ms Pulse 25g
<b>RoHS Status:</b>	Following EU Directive 2002/95/EC August 18, 2005 and amendment

## Technical UL/CSA

<b>Maximum Operating Voltage UL/CSA:</b>	Main Circuit 600 V AC
<b>Ampere Rating UL/CSA:</b>	50 A
<b>Horsepower Rating UL/CSA:</b>	(200 V AC) Three Phase 20 Hp (208 V AC) Three Phase 20 Hp (220 ... 240 V AC) Three Phase 25 Hp (440 ... 480 V AC) Three Phase 50 Hp (550 ... 600 V AC) Three Phase 60 Hp
<b>General Use Rating UL/CSA:</b>	(600 V AC) 50 A
<b>Connecting Capacity Main Circuit UL/CSA:</b>	Flexible 1x 10 ... 2/0 AWG Flexible 1/2x 10 ... 1/0 AWG Stranded 1x 10 ... 2/0 AWG Stranded 1/2x 10 ... 1/0 AWG
<b>Tightening Torque UL/CSA:</b>	Main Circuit 35 ... 53 in-lb

## Additional Information

<b>Actuator Type:</b>	Rotary Handle
<b>Connecting Capacity-Main Circuit:</b>	Flexible with Ferrule 1x 2.5 ... 50 mm <sup>2</sup> Flexible with Ferrule 2x 2.5 ... 35 mm <sup>2</sup> Solid 1/2x 2.5 ... 16 mm <sup>2</sup> Stranded 1x 10 ... 70 mm <sup>2</sup> Stranded 2x 10 ... 50 mm <sup>2</sup>
<b>Conventional Free-air Thermal Current (I<sub>th</sub>):</b>	Main Circuit 50 A
<b>Degree of Protection:</b>	Housing IP20 Main Circuit Terminals IP00
<b>Electrical Durability:</b>	25000 cycle
<b>IIT Publishing Status:</b>	Level 0 - Information enabled
<b>Mechanical Durability:</b>	50000 cycle
<b>Mounting on DIN Rail:</b>	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715
<b>Mounting Position:</b>	Position 1 to 6
<b>Number of Poles:</b>	3
<b>Number of Protected Poles:</b>	3
<b>Pollution Degree:</b>	3
<b>Power Loss:</b>	at Rated Operating Conditions per Pole 3.4 ... 6.7 W
<b>Product Main Type:</b>	MS497
<b>Product Name:</b>	Manual Motor Starter
<b>Rated Current (I<sub>n</sub>):</b>	50 A
<b>Rated Frequency (f):</b>	Main Circuit 50 Hz Main Circuit 60 Hz
<b>Rated Impulse Withstand Voltage (U<sub>imp</sub>):</b>	Main Circuit 6 kV
<b>Rated Instantaneous Short-Circuit Current Setting (I<sub>i</sub>):</b>	819 A
<b>Rated Insulation Voltage (U<sub>i</sub>):</b>	690 V
<b>Rated Operational Current (I<sub>e</sub>):</b>	50 A
<b>Rated Operational Current AC-3 (I<sub>e</sub>):</b>	50 A
<b>Rated Operational Power AC-3 (P<sub>e</sub>):</b>	(400 V) Three Phase 30 kW
<b>Rated Operational Voltage:</b>	Main Circuit 690 V AC Main Circuit 450 V DC
<b>Rated Service Short-Circuit Breaking Capacity (I<sub>cs</sub>):</b>	(230 V AC) 100 kA (400 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 7.5 kA (690 V AC) 4 kA
<b>Rated Service Short-Circuit Breaking Capacity, in % of I<sub>cu</sub> (I<sub>cs</sub>):</b>	100 %
<b>Rated Ultimate Short-Circuit Breaking Capacity (I<sub>cu</sub>):</b>	(230 V AC) 100 kA (400 V AC) 100 kA (440 V AC) 70 kA (500 V AC) 15 kA (690 V AC) 7.5 kA
<b>Rated Uninterrupted Current (I<sub>u</sub>):</b>	50 A
<b>Recommended Screw Driver:</b>	Hexagon 4
<b>RoHS Date:</b>	0016
<b>Setting Range:</b>	45 ... 63 A
<b>Standards:</b>	IEC/EN 60947-1 IEC/EN 60947-2 IEC/EN 60947-4-1 UL 508 CSA 22.2 No. 14
<b>Tightening Torque:</b>	Main Circuit 4 ... 6 N·m
<b>Wire Stripping Length:</b>	Main Circuit 17 mm

## Certificates and Declarations (Document Number)

<b>ATEX Certificate:</b>	1SAA937000-3901
<b>BV Certificate:</b>	1SAA937000-0202
<b>CCC Certificate:</b>	1SAA937001-3803
<b>cUL Certificate:</b>	cUL_E195536
<b>Data Sheet, Technical Information:</b>	1SBC100173C0201
<b>Data Sheet, Technical Information (Part 2):</b>	1SAM500503F0007

Data Sheet, Technical Information 9AKK105713A1104  
(Part 3):

Declaration of Conformity - CE:	1SAD938503-0050
DNV Certificate:	1SAA937000-0301
EAC Certificate:	1SAA937001-2703
GL Certificate:	1SAA937000-0404
GOST Certificate:	1SAA937000-2703
LR Certificate:	1SAA937000-0504
RMRS Certificate:	1SAA918000-0703
RoHS Information:	1SAA918002-4401
UL Certificate:	UL_E167205 UL_E195536

## Classifications

eClass:	7.0 27370401
ETIM 4:	EC000074 - Motor protective circuit-breaker
ETIM 5:	EC000074 - Motor protective circuit-breaker
Object Classification Code:	F
UNSPSC:	39121521





Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

<b>Product</b>	<b>Code</b>	<b>Reference</b>	<b>Product link</b>
MS497-63 Manual Motor Starter	1SAM580000R1007	MS497-63	<a href="#">Buy on EAN</a>