

Rittal – The System.

Faster – better – everywhere.



SV 9340.320 OM adaptors

State: 21/02/2022 (Source: rittal.com/com-en)

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



SV 9340.320 - OM adaptors with connection cables



Features

| | |
|--|--|
| Material | Polyamide Fire protection corresponding to UL 94-V0 |
| Colour | Chassis: RAL 7035 |
| Length | AWG 12 |
| Rated current max. | 25 A |
| Rated operating voltage | 690 V, 3~ |
| For busbar systems with centre-to-centre spacing | 60 mm |
| Connection cables (length) | 130 mm |
| Support rail type | TS 45D |
| Note | The technical data may vary for UL applications |
| Number of poles | 3-pole |
| Dimensions | Width: 45 mm Height: 208 mm |
| Support rails Qty/height | 2 / 10 mm |
| To fit busbars | with cross-section height: 5, 10 mm |
| Weight/pack | 0.26 kg |
| Packs of | 1 Stück |
| ETIM 7.0 | EC001531 |

Features

ECLASS 8.0

27370304

Approvals

Approvals

Lloyds Register of Shipping
UL + C-UL

Certificates

EAC

Explanations

Declaration of conformity