

Specyfikacje



Eaton 260129

Eaton Moeller series NZM - Molded Case Circuit Breaker. Rotary handle, lockable, size 3

General specifications

PRODUCT NAME	Eaton Moeller series NZM operating element
CATALOG NUMBER	260129
EAN	4015082601294
PRODUCT LENGTH/DEPTH	108 mm
PRODUCT HEIGHT	124 mm
PRODUCT WIDTH	140 mm
PRODUCT WEIGHT	0.881 kg
COMPLIANCES	IEC UL/CSA RoHS conform
CERTIFICATIONS	UL489 CE marking UL (Category Control Number DIHS) UL listed CSA (File No. 22086) CSA-C22.2 No. 5-09 UL (File No. E140305) CSA (Class No. 1437-01) IEC60947 CSA certified
MODEL CODE	NZM3-XDV



Powering Business Worldwide

Delivery program

TYPE	<ul style="list-style-type: none">• Accessory• Rotary handle on circuit-breaker
-------------	--

FEATURES	Lockable Standard: black / gray
-----------------	------------------------------------

SPECIAL FEATURES	<ul style="list-style-type: none">• Complete with rotary drive• Can be combined with insulating surround• MODAN handle position detection by wire release can be retrofitted• Makes it possible to operate the switch with a rotational movement and provides locking facilities
-------------------------	---

FRAME	NZM3
--------------	------

FITTED WITH:	Padlock
---------------------	---------

SUITABLE FOR	Switch disconnecter Power circuit breaker
---------------------	--

USED WITH	NZM3(-4), PN3(-4), N(S)3(-4)
------------------	------------------------------

Technical Data - Mechanical

COLOR	Black
--------------	-------

DEGREE OF PROTECTION / NEMA ENCLOSURE TYPE	IP20 4X. 12
---	----------------

ACTIVATION TYPE	Rotary handle
------------------------	---------------

LOCKING FACILITY	Lockable on the 0 position on the switch using up to 3 padlocks
-------------------------	---

SPECIAL FEATURES	<ul style="list-style-type: none">• Complete with rotary drive• Can be combined with insulating surround• MODAN handle position detection by wire release can be retrofitted• Makes it possible to operate the switch with a rotational movement and provides locking facilities
-------------------------	---

Design verification as per IEC/EN 61439

10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
10.10 TEMPERATURE RISE	The panel builder is responsible for the

Do pobrania

INSTRUKCJE MONTAŻU	eaton-nzm3-xd-v-kl-rotary-drive-il01219014z.pdf
MODELE MCAD	eaton-cadenas-front_view-nzm3_xdv_front.pra
	eaton-cadenas-path-circuit breaker-nzm3_xdv.3db
	eaton-cadenas-side_view-nzm3_xdv_side.pra
	DA-CD-nzm3_xd DA-CS-nzm3_xd
RYSUNKI	eaton-circuit-breaker-rotary-handle-nzm-rotary-handle-dimensions-003.eps
	eaton-circuit-breaker-rotary-handle-nzm-rotary-handle-3d-drawing-005.eps

	temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

NAZWA PROJEKTU:

NUMER PROJEKTU:

PRZYGOTOWANE PRZEZ:

DATA:



Eaton Corporation plc Eaton House
 30 Pembroke Road
 Dublin 4, Irlandia
 Eaton.com

© 2026 Eaton. Wszelkie prawa zastrzeżone.

Najnowsze informacje o produktach i wsparciu znajdują się na naszych mediach społecznościowych.

