

# Product data sheet

Specifications



Control station, Harmony XAW, metal with fiberglass, emergency stop function, turn to release, 1 red mushroom 40mm, 1NC + 1NC, ATEX

XAWG178EX

## Main

Range of product	Harmony XAW
Product or component type	Complete control station
Device short name	XAWG
Control station application	Emergency stop function
Material	Glass fibre reinforced
Reset	Turn to release
Control station composition	1 mushroom head Ø 40 mm push-button, red, trigger action 1 NC + 1 NC

## Complementary

Colour of base of enclosure	Black
Colour of cover	Black
Cable entry	1 entry for ISO M20 cable gland
Width	80 mm
Depth	70 mm
Height	146 mm
Product weight	0.660 kg
Marking	Ex tb IIIC T85°C Db IP65
Mechanical durability	300000 cycles
Short-circuit protection	10 A cartridge fuse type gG
[Ie] rated operational current	3 A at 240 V, AC-15, A600 6 A at 120 V, AC-15, A600 0.1 A at 600 V, DC-13, Q600 0.27 A at 250 V, DC-13, Q600 0.55 A at 125 V, DC-13, Q600 1.2 A at 600 V, AC-15, A600

## Environment

Ambient air temperature for operation	-20...60 °C
Overvoltage category	II conforming to IEC 60536
IP degree of protection	IP65 conforming to IEC 60529
Standards	EN 60079-0:2009 EN 60079-31:2009

EN 60947-5-4  
EN 61000-6-2  
EN/IEC 60947-1  
EN/IEC 60947-5-1  
IEC 60079-0:2007  
IEC 60079-31:2008  
EN 60947-5-5  
EN/ISO 13850

---

<b>Directives</b>	94/9/EC - ATEX directive
<b>Dust zone</b>	Zone 21 - 22
<b>Product certifications</b>	INERIS 04ATEX0023X

---

## Offer Sustainability

---

<b>REACH Regulation</b>	<a href="#">REACH Declaration</a>
<b>EU RoHS Directive</b>	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
<b>Mercury free</b>	Yes
<b>China RoHS Regulation</b>	<a href="#">China RoHS declaration</a>
<b>RoHS exemption information</b>	<a href="#">Yes</a>

---

## Recommended replacement(s)