



## Delivery program

### APPLICATION

- Branch circuits, not as BCPD
- Switchgear for industrial and advanced commercial applications
- xEffect - Switchgear for industrial and advanced commercial applications

<b>NUMBER OF POLES</b>	Single-pole
<b>NUMBER OF POLES (TOTAL)</b>	1
<b>NUMBER OF POLES (PROTECTED)</b>	1
<b>TRIPPING CHARACTERISTIC</b>	C
<b>RELEASE CHARACTERISTIC</b>	C
<b>AMPERAGE RATING</b>	6 A
<b>TYPE</b>	<ul style="list-style-type: none"> <li>• FAZ</li> <li>• Miniature circuit breaker</li> </ul>

## Technical Data - Electrical

<b>VOLTAGE TYPE</b>	AC
<b>VOLTAGE RATING</b>	240 V AC / 415 V AC
<b>VOLTAGE RATING AT DC</b>	60 V DC (per pole)
<b>VOLTAGE RATING (IEC/EN 60898-1)</b>	240 VAC
<b>VOLTAGE RATING (UL)</b>	277 V
<b>VOLTAGE RATING (UL CSA 13)</b>	277 V AC; 48 V DC
<b>RATED OPERATIONAL VOLTAGE (UE) - MAX</b>	230 V
<b>OPERATIONAL VOLTAGE (IEC/EN 60947-2) - MAX</b>	254 VAC
<b>RATED INSULATION VOLTAGE (UI)</b>	440 V
<b>RATED IMPULSE WITHSTAND VOLTAGE (UIMP)</b>	4 kV
<b>FREQUENCY RATING - MIN</b>	50 Hz
<b>FREQUENCY RATING - MAX</b>	60 Hz
<b>RATED SWITCHING CAPACITY (IEC/EN 60947-2) AT MAX VOLTAGE RATING</b>	10 kA
<b>RATED SWITCHING CAPACITY (IEC/EN 60947-2)</b>	15 kA
<b>RATED SWITCHING CAPACITY (IEC/EN 60898-1)</b>	10 kA
<b>OPERATIONAL SWITCHING CAPACITY</b>	7.5 kA
<b>BREAKING CAPACITY</b>	10 kA (UL1077)
<b>ADMISSIBLE BACK-UP FUSE - MAX</b>	125 A gL/gG
<b>SELECTIVITY CLASS</b>	3
<b>LIFESPAN, ELECTRICAL</b>	10000 operations
<b>OVERVOLTAGE CATEGORY</b>	III
<b>POLLUTION DEGREE</b>	2
<b>DIRECTION OF INCOMING SUPPLY</b>	As required

## Technical Data - Mechanical

<b>FRAME</b>	45 mm
<b>ENCLOSURE WIDTH</b>	80 mm
<b>WIDTH IN NUMBER OF MODULAR SPACINGS</b>	1
<b>BUILT-IN DEPTH</b>	70.5 mm
<b>MOUNTING WIDTH PER POLE</b>	17.5 mm
<b>MOUNTING WIDTH</b>	17.5 mm
<b>MOUNTING METHOD</b>	Top-hat rail IEC/EN 60715
<b>MOUNTING POSITION</b>	As required
<b>DEGREE OF PROTECTION</b>	UL/CSA Type: - IP20 IP40 (when fitted) IP20 (IEC)
<b>TERMINALS (TOP AND BOTTOM)</b>	Twin-purpose terminals
<b>CONNECTABLE CONDUCTOR CROSS SECTION (SOLID-CORE) - MIN</b>	1 mm <sup>2</sup>
<b>CONNECTABLE CONDUCTOR CROSS SECTION (SOLID-CORE) - MAX</b>	25 mm <sup>2</sup>
<b>CONNECTABLE CONDUCTOR CROSS SECTION (MULTI-WIRED) - MIN</b>	1 mm <sup>2</sup>
<b>CONNECTABLE CONDUCTOR CROSS SECTION (MULTI-WIRED) - MAX</b>	25 mm <sup>2</sup>
<b>TERMINAL CAPACITY OF SCREW TERMINALS FOR MAIN CABLE</b>	10 mm <sup>2</sup> (2x)
<b>TERMINAL CAPACITY (CONTROL CABLE)</b>	25 mm <sup>2</sup> (1x)
<b>TERMINAL PROTECTION</b>	Finger and hand touch safe, DGUV VS3, EN 50274
<b>BUSBAR MATERIAL THICKNESS</b>	0.8 mm - 2 mm

## Design verification as per IEC/EN 61439 - technical data

<b>RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)</b>	6 A
<b>HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT</b>	0 W
<b>EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT</b>	1.5 W
<b>STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT</b>	0 W
<b>HEAT DISSIPATION CAPACITY</b>	0 W
<b>AMBIENT OPERATING TEMPERATURE - MIN</b>	-25 °C
<b>AMBIENT OPERATING TEMPERATURE - MAX</b>	75 °C

## Design verification as per IEC/EN 61439

<b>10.2.2 CORROSION RESISTANCE</b>	Meets the product standard's requirements.
<b>10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES</b>	Meets the product standard's requirements.
<b>10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT</b>	Meets the product standard's requirements.
<b>10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS</b>	Meets the product standard's requirements.
<b>10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION</b>	Meets the product standard's requirements.
<b>10.2.5 LIFTING</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.2.6 MECHANICAL IMPACT</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.2.7 INSCRIPTIONS</b>	Meets the product standard's requirements.
<b>10.3 DEGREE OF PROTECTION OF ASSEMBLIES</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.4 CLEARANCES AND CREEPAGE DISTANCES</b>	Meets the product standard's requirements.
<b>10.5 PROTECTION AGAINST ELECTRIC SHOCK</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS</b>	Is the panel builder's responsibility.
<b>10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS</b>	Is the panel builder's responsibility.
<b>10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH</b>	Is the panel builder's responsibility.
<b>10.9.3 IMPULSE WITHSTAND VOLTAGE</b>	Is the panel builder's responsibility.
<b>10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL</b>	Is the panel builder's responsibility.
<b>10.10 TEMPERATURE RISE</b>	The panel builder is responsible for the

## Additional information

<b>CURRENT LIMITING CLASS</b>	3
<b>FEATURES</b>	Additional equipment possible
<b>SPECIAL FEATURES</b>	Ambient temperature hint: a 1 °C increase results in a 0.5% linear reduction of current carrying capacity
<b>USED WITH</b>	Miniature circuit breaker FAZ

	temperature rise calculation. Eaton will provide heat dissipation data for the devices.
<b>10.11 SHORT-CIRCUIT RATING</b>	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
<b>10.12 ELECTROMAGNETIC COMPATIBILITY</b>	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
<b>10.13 MECHANICAL FUNCTION</b>	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Do pobrania

CHARACTERISTIC CURVE	<a href="#">eaton-mcb-xeffect-faz-characteristic-curve-002.eps</a>
	<a href="#">eaton-xeffect-faz-mcb-characteristic-curve.jpg</a>
	<a href="#">eaton-mcb-current-xeffect-faz-characteristic-curve.eps</a>
	<a href="#">eaton-mcb-current-xeffect-faz-characteristic-curve-002.eps</a>
	<a href="#">eaton-mcb-tripping-characteristic-xeffect-faz-characteristic-curve-002.eps</a>
	<a href="#">eaton-mcb-xeffect-faz-characteristic-curve.eps</a>

DEKLARACJE ZGODNOŚCI	<a href="#">eaton-mcb-declaration-of-conformity-eu250395en.pdf</a>
----------------------	--

INSTRUKCJE MONTAŻU	<a href="#">eaton-rccb-rcho-g9-il019140zu.pdf</a>
--------------------	---

MODELE ECAD	<a href="#">ETN.FAZ-C6_1</a>
-------------	------------------------------

MODELE MCAD	<a href="#">eaton-non-selective-universal-mcb-mcad-drawings-faz-pls-1p.dwg</a>
	<a href="#">faz_1p.stp</a>

PEP ECO-PASSPORT	<a href="#">EATO-00047-V01.01-EN</a>
------------------	--------------------------------------

RYSUNKI	<a href="#">eaton-xeffect-faz-mcb-dimensions.jpg</a>
	<a href="#">eaton-mcb-xeffect-faz-dimensions.eps</a>
	<a href="#">eaton-xeffect-faz-mcb-3d-drawing-010.jpg</a>
	<a href="#">eaton-xeffect-faz-mcb-3d-drawing-009.jpg</a>
	<a href="#">eaton-xeffect-faz-mcb-3d-drawing-002.jpg</a>
	<a href="#">eaton-mcb-faz-xeffect-faz-3d-drawing.eps</a>

SCHEMATY POŁĄCZEŃ	<a href="#">eaton-xpole-mmc4-6-m-mcb-wiring-diagram-002.jpg</a>
	<a href="#">eaton-mcb-xeffect-faz-wiring-diagram.eps</a>

---

**NAZWA PROJEKTU:**

**NUMER PROJEKTU:**

**PRZYGOTOWANE PRZEZ:**

**DATA:**

---



**Eaton Corporation plc** Eaton House  
30 Pembroke Road  
Dublin 4, Irlandia  
Eaton.com

Najnowsze informacje o produktach i wsparciu znajdują się na naszych mediach społecznościowych.



© 2025 Eaton. Wszelkie prawa zastrzeżone.