

**Rittal – The System.**

Faster – better – everywhere.



**SV 9343.200**

**NH fuse-switch-disconnectors, size  
00 to 3**

State: 21/02/2022 (Source: [rittal.com/com-en](http://rittal.com/com-en))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# SV 9343.200 - NH fuse-switch-disconnectors, size 00 to 3

## Features

Material	Polyamide Fire protection corresponding to UL 94 Contact tracks: Electrolytic copper, silver-plated
Colour	Chassis: RAL 7035 Cover: RAL 7035/7001
Clamping area for laminated copper bars	Width: 32 mm Height: 10 mm
Note	Connection of sector-shaped conductors 120 – 300 mm <sup>2</sup> .
For busbar systems with centre-to-centre spacing	60 mm
Cable outlet	Top/bottom
Type of electrical connection	Box terminal
Rated operating current (max.)	400 A
NH construction size	2
Note	The technical data may vary for UR applications. Applications to UR only in conjunction with "Special Purpose Fuses".
Test specification	IEC/DIN EN 60 947-3 DIN EN 60 269-2 (fuse inserts)
Dimensions	Width: 210 mm Height: 298 mm
Connection for round conductor cross-sections	95 - 300 mm <sup>2</sup>
To fit busbars	with cross-section height: 5, 10 mm
Clamping area for laminated copper bars	20 mm
Weight/pack	3.64 kg
Packs of	1 Stück

# Features

---

ETIM 7.0	EC001040
----------	----------

---

ECLASS 8.0	27371401
------------	----------

# Approvals

---

Approvals	C-UR CQC-CCC UR + C-UR
-----------	------------------------------

---

Certificates	EAC
--------------	-----

---

Explanations	Declaration of conformity
--------------	---------------------------